RAVENOL ATF 8HP Fluid

Kategorie: Gear oil for automatic transmissions

Artikelnummer: 1211124

Oil type: Synthetic

Recommendations: Acura 08200-9016A, Acura ATF Type 3.0, ATF L 12108, BMW 83222289720, BMW 83222305397 (83222152426), BMW ATF 3+, Fiat 9.55550-AV5, Honda 08200-9017, Honda ATF Type 3.1, Land Rover LR023288, Land Rover LR023289, Mopar 68157995AB, Mopar 68218925AA, VW/Audi G 055 162, VW/Audi G 060 162 A2, VW/Audi G 060 162 A1, VW/Audi G 060 162 A6, ZF S671 090 312, ZF TE-ML 11 9HP28, ZF TE-ML 11 9HP48, ZF TE-ML 11 9HP50

Application: Passenger car



1L | 1211124-001
4L | 1211124-004
10L | 1211124-010
20L | 1211124-020
20L | 1211124-B20
60L | 1211124-060
60L | 1211124-D60
208L | 1211124-208
208L | 1211124-D28
1000L | 1211124-700

RAVENOL ATF 8HP Fluid is a synthetic ATF (Automatic Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the automatic transmission.

RAVENOL ATF 8HP Fluid is a automatic transmission oil ATF of the latest generation for all 8 speed automatic transmissions of ZF. It guarantees in any mode for maximum wear protection.

RAVENOL ATF 8HP Fluid is green colored.

Application instructions

RAVENOL ATF 8HP Fluid is suitable for use in automatic ZF transmission of 8HP-Series 8HP45, 8HP55, 6HP26, 8HP70, 8HP90, also for ZF transmission 6-stroke automatic 6HP-series - 6HP19X for AUDI Q7, 6HP19A, 6HP28AF. It is also suitable in ZF transmission series 9HP28, 9HP48, 9HP50.

Please observe OEM Part Numbers.

Characteristics

- Very good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- Very good oxidation stability
- Protection against wear, corrosion and foam formation
- Good balanced coefficient of friction
- A high thermal and oxidative stability
- An excellent cooling capacity

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		grün	VISUELL
Density at 20 °C	kg/m³	838,5	EN ISO 12185
Pourpoint	°C	-48	DIN ISO 3016