RAVENOL CVT Fluid

Kategorie: Gear oil for automatic transmissions

Artikelnummer: 1211110

Oil type: Synthetic

Recommendations: BMW CVT EZL 799A, Chery 018CHA/QR018CHA, Chery 025CHA/QR025CHA, Chery 025CHA-4004011AA10, Chery 025CHC/QR025CHC, Chery CVT18, Chery CVT25, Chery CVTF WCF-1, Ford Five Hundred CFT30, Ford EU WSS-M2C-928 A, Ford Focus C-Max CFT23, Ford USA WSS-M2C933-A, Ford XT-7-QCFT Freestyle, HMMF Ultra Fluid 08260-99904, HMMF Ultra Fluid 08260-99907, Honda CVT Fluid 08200-9006, Hunan Jianglu and Rongda 150R, Hunan Jianglu and Rongda R0CF15A2, Hunan Jianglu and Rongda R0CF15A3, Hunan Jianglu and Rongda RDC15, Hunan Jianglu and Rongda RDC15-FB, Mazda TFF CVT Fluid TC JWS3320 K020-W0-051W, MB 236.20 (A 001 989 46 03), Mini Cooper CVT, Nissan CVT Fluid NS-1, Nissan KLE50 00002, Nissan KLE50 00004, Opel/GM 1940713, Punch Powertrain VT1F, Punch Powertrain VT2, Punch Powertrain VT3, Subaru CVT Lineartronic II K0425Y0711, Subaru i-CVT Fluid K0415-YA090, Suzuki S-CVT 99000-22801-000, VW TL 52180, Toyota CVT Fluid TC 08886-02105, VW G 052 516 A2, VW/Audi G 052 180 A1, VW/Audi G 052 180 A2, VW/Audi G 052 180 A6

Application: Passenger car



1L | 1211110-001
4L | 1211110-004
10L | 1211110-010
20L | 1211110-020
20L | 1211110-B20
60L | 1211110-060
60L | 1211110-D60
208L | 1211110-208
208L | 1211110-D28
1000L | 1211110-700

RAVENOL CVT Fluid is a synthetic ATF for the latest generation of CVT transmission.

RAVENOL CVT Fluid guarantees an optimum of power transmission.

RAVENOL CVT Fluid is based on high-quality hydrocrack oils with special additives and inhibition to ensure the proper operation of the automatic transmission.

Application instructions

RAVENOL CVT Fluid was developed for use in CVT transmission (Steel Belt Continuously Variable Transmission).

RAVENOL CVT Fluid ensures a stable viscosity under high mechanical stress in the transmission elements (push belt).

Characteristics

- Very good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- Very low pour point
- Very good oxidation stability
- Protection against corrosion and foam formation
- Good balanced coefficient of friction
- Neutral behaviour towards sealing materials
- Neutral behaviour by inhibition to non-ferrous metals

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm^2/s	7,3	DIN 51659-2
Viscosity at 40 °C	mm^2/s	35,5	DIN 51659-2
Viscosity Index VI		175	DIN ISO 2909
Density at 20 °C	kg/m^3	841,0	EN ISO 12185
Pourpoint	°C	-48	DIN ISO 3016