RAVENOL LTC HOT CLIMATE-15°C Protect C12++



Kategorie: Radiator antifreeze

Artikelnummer: 1410127

Recommendations: Chrysler MS-90032, DTFR 29C120 (325.5), DTFR 29D120 (326.5), MAN 324 Si-OAT, MB 325.5, MB 326.6 (Premix), Mopar 68163848AA, Mopar 68163849AA, Scania TB 1451, VW G 012 A8G M1, VW G 012 A8G M8, VW G 012 A8G M9, VW G 013 A8J M1, VW G 013 A8J M8, VW G 013 A8J M9, VW TL 774-G (entspricht G12++), VW TL 774-J (entspricht G13)

Application: Passenger car

RAVENOL LTC Lobrid Tech. Coolant HOT CLIMATE -15°C is a ready to use, prediluted with water, eco-friendly 1.2- Ethanediol (monoethylene glycol) based coolant for cooling circuits in combustion engines which provides maintenance-free corrosion and frost protection. This product is formulated based on a proven inhibitor development by combining silicates with the organic additive technology OAT as an extended life coolant.

1.5L | 1410127-150
5L | 1410127-005
20L | 1410127-020
60L | 1410127-060
208L | 1410127-208
1000L | 1410127-700

RAVENOL LTC Lobrid Tech. Coolant HOT CLIMATE -15°C is free from 2-ethylhexanoic acid, borate, nitrite, amine and phosphate.

The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection.

That is why manufacturers subject antifreeze to lengthy corrosion and cavitation tests.

RAVENOL LTC Lobrid Tech. Coolant HOT CLIMATE -15°C protects the cooling system from rust, frost, and in summer, from overheating.

Application instructions

RAVENOL LTC Lobrid Tech. Coolant HOT CLIMATE -15°C is a prediluted coolant with frost and rust protection for year-round use in automotive engines.

Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

Instructions: Add **RAVENOL LTC Lobrid Tech. Coolant HOT CLIMATE -15°C** to radiator to fill line.

Characteristics

- Excellent for all-aluminium engines
- Good reserve alkalinity
- Premium corrosion additives for optimal rust protection for all metals and metal alloys used in cooling systems, including aluminium
- Prevents sediments and foaming in the cooling system
- Compatible with elastomers used in automotive radiators
- Can be mixed with other coolant types

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		violett	VISUELL
Density at 20 °C	kg/m³	1043,0	EN ISO 12185
Freezing point	°C	-15	ASTM D1177
pH - value at 20 °C		8,0	ASTM D1287