RAVENOL ATF J2/S Fluid

Kategorie: Gear oil for automatic transmissions

Artikelnummer: 1211115

Oil type: Synthetic

Recommendations: Mitsubishi 4031610 ATF Fluid J3, Mitsubishi MZ313771 ATF Fluid J2, Nissan 999MP-MTJ00P Matic Fluid J, Nissan 999MP-MTS00P Matic Fluid S, Nissan KE908-99932 Matic Fluid J, Nissan KLE2300002 Matic Fluid J, Nissan KLE24 00002 Matic Fluid S, Renault Matic J6

Application: Passenger car



1L | 1211115-001
4L | 1211115-004
10L | 1211115-010
20L | 1211115-020
20L | 1211115-B20
60L | 1211115-060
60L | 1211115-D60
208L | 1211115-208
208L | 1211115-D28
1000L | 1211115-700

RAVENOL ATF J2/S Fluid is a synthetic ATF (Automatic Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the automatic transmission.

RAVENOL ATF J2/S Fluid is specifically designed for all 5, 6 and 7-speed JATCO automatic transmissions.

RAVENOL ATF J2/S Fluid ensures maximum wear protection and smooth shifting in all conditions.

RAVENOL ATF J2/S Fluid is red colored.

Application instructions

RAVENOL ATF J2/S Fluid is designed specifically for use in JATCO automatic transmissions as follows; JF613E - Renault gearbox AJ0 Laguna, Scenic, Espace, Latitude; Nissan Qashqai transmission AJ0; Mitsubishi Outlander Transmission F6AJA and W6AJA; JR710E and JR711E - Infiniti FX50, EX37, NISSAN FAIR LADY Z, SKYLINE, FUGA.

Characteristics

- Excellent lubricity even at low temperatures in winter
- High and stable viscosity index
- Very good oxidation stability
- Extensive protection against wear, corrosion and foaming
- High thermal and oxidative stability
- An excellent cooling capability

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		rot	VISUELL
Density at 20 °C	kg/m³	838,0	EN ISO 12185
Pourpoint	°C	-51	DIN ISO 3016